



Representative

Catalog Number: 3139
Product ID: 7TAA106030R0016
UPC Number: 78621003139
Status: Active

Metal-Clad and Armored Cable Fitting, 90 Degree Bend, Trade Size 1-1/2 Inch, Knockout Size 1-1/2 Inch, Cable Range 1.812 to 2.031 Inch, Malleable Iron with Zinc Plating, Nylon Insulated

- All the advantages of the straight connector with only one screw to tighten, except in the larger sizes where there are two.
- A peep hole on top provides for easy inspection of the ABC bushing.
- Narrow design makes it easy to install connectors in adjacent knockouts.
- To connect and effectively bond armored cable or flexible metal conduit to a box or an enclosure.

North American Specifications (UNSPSC)

| | |
|------------------|---|
| UNSPSC | 39121419 Flex connectors |
| IGCC | 4573 Flex connectors |
| Brand Name | T&B |
| Type | Armored Cable/Flexible Metal Conduit Fittings |
| Special Features | By Far The Easiest and Best to Install When Making Sharp Bends At The Enclosure or Equipments |
| Application | For Use with Armored Cable and Flexible Metal Conduit |
| Standard | UL E23018, CSA |
| Size | 1-1/2 Inch |
| Connection | 90 Degree |
| Conductor Range | 1.812 to 2.031 Inch |
| Material | Malleable Iron |
| Finish | Electro Zinc Plated |
| Color | Metallic |
| Insulation | Nylon |

European Specifications (ETIM)

| | |
|---|--|
| ETIM | EC001180 Screw connection for protective metallic hose |
| Nominal size in inch | 1 1/2 inch |
| Model | 90°-elbow |
| Revolving thread | N |
| Construction type | External thread |
| Connection type screw connection to housing | Other |
| Material housing | Other |
| Surface protection | Zinc coated |
| Thread length | 30.16mm |

Packaging

| | |
|---------------------------|------------------|
| Inner Quantity | 1 |
| Inner Dimensions (inches) | 6x4.5x3 |
| Outer Quantity | 10 |
| Outer Dimensions (inches) | 21.5x10x6.75 |
| Weight Uom | 175 lbs. per 100 |

Documents / Support Tools

| | |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet US | Available on Website |
| Technical Drawing / Data Sheet Canada | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com