



Representative

**Catalog Number:** 3312-TB  
**Product ID:** 7TAA106080R0010  
**UPC Number:** 78621003312  
**EAN Number:** 05414363141167  
**Status:** Active

1/2 Inch, Two Screw Connector, Steel, 1/2 Inch Knockout, CSA Certified for Aluminum, Grounding Type, For Sheathed Cable 2 #8, 3 #8 4 #10, Cable Opening .813 Inch to .938 Inch

- The armor gripping saddle stays open by itself when cable is being inserted.

### Header

3D Model Available on Website

### North American Specifications (UNSPSC)

UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B
Type	Armored Cable/Flexible Metal Conduit Fittings
Special Features	Formed Steel Body with Carefully Round Bushing.
Application	For Use with Armored Cable and Flexible Metal Conduit.
Standard	UL E1383, CSA
Size	1/2 Inch
Connection	Straight
Conductor Range	0.813 to 0.937 Inch
Material	Steel
Finish	Zinc Plated
Color	Metallic

### European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1/2 inch
Model	Straight
Revolving thread	N
Material housing	Other
Surface protection	Untreated
Approved in combination with protective conduit CSA	Y

### Packaging

Inner Quantity	50
Inner Dimensions (inches)	8x5.1x4.1
Outer Quantity	100
Outer Dimensions (inches)	8.5x5.5x8.7
Weight Uom	102 lbs. per 1000

### Documents / Support Tools

Technical Data Sheet CA	Available on Website
Technical Data Sheet Global	WSD-001571

For further technical assistance, please contact us...

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321

