



### Main

Range of product	GV3
Product or component type	Auxiliary contact block
Product compatibility	GV3ME80
Pole contact composition	1 NO + 1 NC
Quantity per set	Set of 10

### Complementary

Mounting location	Right side
Auxiliary contacts operation	Instantaneous
[Ui] rated insulation voltage	600 V - for control circuit - conforming to UL 508 600 V - for control circuit - conforming to CSA C22-2 No 14 690 V - for control circuit - conforming to IEC 60947-1
[Ue] rated operational voltage	690 V
[Ith] conventional free air thermal current	5 A for control circuit conforming to CSA C22-2 No 14 5 A for control circuit conforming to UL 508 6 A for control circuit conforming to IEC 60947-5-1
Protection type	GB2CB... circuit breaker rating according to operational current for $U_e \leq 415$ V for control circuit GG fuse $\leq 10$ A for control circuit
Mechanical durability	100000 cycles
Rated operational power in VA	350 VA at 48 V AC-11 - electrical durability: 100000 cycles - for control circuit 400 VA at 690 V AC-11 - electrical durability: 100000 cycles - for control circuit 500 VA at 110...127 V AC-11 - electrical durability: 100000 cycles - for control circuit 700 VA at 440 V AC-11 - electrical durability: 100000 cycles - for control circuit 700 VA at 500 V AC-11 - electrical durability: 100000 cycles - for control circuit 800 VA at 220...240 V AC-11 - electrical durability: 100000 cycles - for control circuit 850 VA at 380...415 V AC-11 - electrical durability: 100000 cycles - for control circuit
Rated operational power in W	120 W at 220 V DC-11 - electrical durability: 100000 cycles - for control circuit 140 W at 110 V DC-11 - electrical durability: 100000 cycles - for control circuit 180 W at 24 V DC-11 - electrical durability: 100000 cycles - for control circuit 180 W at 60 V DC-11 - electrical durability: 100000 cycles - for control circuit 240 W at 48 V DC-11 - electrical durability: 100000 cycles - for control circuit
Connections - terminals	Control circuit: connector 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid Control circuit: connector 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid Control circuit: connector 1 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Control circuit: connector 2 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Control circuit: connector 1 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Control circuit: connector 2 cable 0.75...1.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end
Product weight	0.06 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.