

161-64310



**Article Number:** 161-64310

**Helawrap, HWPP20, 3/4" (20mm) Dia., PP, Black, 100ft/Reel**



Download drawing



Download spec sheet



Download tech sheet

## Base Data

**Local Order Number** 161-64310

**Type** HWPP20

**Color** Black (BK)

- Features and Benefits**
- Unique open design for easy branch-offs at any point along the harness.
  - Overwrap formation provides abrasion protection and accommodates multiple bundle configurations.
  - Flexible construction and design eliminates pinch points and minimizes bending fatigue, making it ideal for applications involving movement and vibration.
  - Split shape allows for future access without disassembly.

**Product Description** The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.

**Short Description** Helawrap, HWPP20, 3/4" (20mm) Dia., PP, Black, 100ft/Reel

## Product Dimensions

**Length L (Imperial)** 100.0 ft

**Length L (Metric)** 30.48 m

**Reel Length (imperial)** 100.0 ft

**Variant** Spiral Binding

**Bundle Diameter Min. (Imperial)** 0.71 "

**Bundle Diameter Min. (Metric)** 18.03 mm

**Bundle Diameter Max. (Imperial)** 0.83 "

**Bundle Diameter Max. (Metric)** 21.08 mm

**Diameter D (imperial)** 0.75 "

**Diameter D (metric)** 20.0 mm

**Nominal Diameter (Imperial)** 3/4 "

**Nominal Diameter (Metric)** 20.0 mm

**Wall Thickness WT (Imperial)** 0.04 "

**Wall Thickness WT (Metric)** 0.95 mm

**Pitch (imperial)** 0.63 "

**Pitch (metric)** 16.0 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 100.0 ft

**Package Quantity (Metric)** 30.48 m

**Carton Quantity** 30.48 m

**Weight (imperial)** 2.56 lbs

**Weight (Metric)** 1.18 kg

---

## Material and Specifications

**Material** Polypropylene (PP)

**Material Shortcut** PP

**Flammability** UL94 HB

**Halogenfree** Yes

**Operating Temperature** -76°F to +230°F (-60°C to +110°C)

**ROHS Compliant** Yes