
Product data sheet Characteristics

XZCR1512062B1

jumper cable XZ - male straight M12 3-pin - female elbowed M12 3-pin - PUR 1m

Price*: 41.10 USD

XZCR1512062B1 has not been replaced. Please contact your customer care center for more information.



⚠ Discontinued

Main		
Accessory / separate part category	Cabling accessory	
Accessory / separate part type	Jumper cable	
Complementary		
Jumper cable end 1	M12 male, :3 pins (straight), fixing: screw-on	
Jumper cable end 2	M12 female, :3 pins (elbowed), fixing: screw-on	
Cable composition	3 x 0.5 mm²	
Cable length	3.28 ft (1 m)	
Wire insulation material	PUR	
Cable outer diameter	0.2 in (5.2 mm)	
System Voltage	30 V AC 36 V DC	
Line Rated Current	4 A	
Insulation resistance	>= 1000 MOhm	
Resistance across terminals	<= 5000 mOhm	
Product weight	0.14 lb(US) (0.065 kg)	
Environment		
IP degree of protection	IP67	
Product certifications	CULus	
Ambient air temperature for operation	-31194 °F (-3590 °C) (static) 23194 °F (-590 °C) (flexing)	
Ambient air temperature for storage	-31212 °F (-35100 °C)	
Ordering and shipping details		
Category	22483 - MACHINE CABLES	

Returnability

GTIN

Discount Schedule

Nbr. of units in pkg.

Package weight(Lbs)

003389110762549

0.1499999999999999

Country of origin	PL	
Offer Sustainability		
RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
Contractual warranty		
Warranty period	18 months	