Product data sheet Characteristics

XAPM24

empty control station - XAP-M - metal - without opening

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 152.00 USD



Main

Range of product	Harmony XAP	
Product or component type	Die-cast empty control station	
Device short name	XAPM	
Product front plate size	80 x 130 mm	
Usable depth	2.93 in (74.5 mm)	
Number of cut-out	Undrilled	
Colour of base of enclosure	Blue	
Colour of cover	Blue	
Material	Zinc alloy	
Cable entry	1 hole with blanking plug for cable gland with <= 0.55 in (14 mm) 1 hole without blanking plug for cable gland with <= 0.55 in (14 mm)	
Product mounting	Flush mounting	
IP degree of protection	IP69 conforming to NF C 20-010 IP65 conforming to IEC 60529 IP69K	

Complementary

Product weight	1.83 lb(US) (0.83 kg)
----------------	-----------------------

Environment

Main		
Range of product	Harmony XAP	
Product or component type	Die-cast empty control station	
Device short name	XAPM	
Product front plate size	80 x 130 mm	
Usable depth	2.93 in (74.5 mm)	
Number of cut-out	Undrilled	
Colour of base of enclosure	Blue	
Colour of cover	Blue	
Material	Zinc alloy	
Cable entry	1 hole with blanking plug for cable gland with <= 0.55 in (14 mm) 1 hole without blanking plug for cable gland with <= 0.55 in (14 mm)	
Product mounting	Flush mounting	
IP degree of protection	IP69 conforming to NF C 20-010	
dog. do di protodion	IP65 conforming to IEC 60529 IP69K	
	IP65 conforming to IEC 60529	
Complementary Product weight	IP65 conforming to IEC 60529 IP69K	
Complementary	IP65 conforming to IEC 60529	
Complementary Product weight	IP65 conforming to IEC 60529 IP69K	
Complementary Product weight Environment	IP65 conforming to IEC 60529 IP69K 1.83 lb(US) (0.83 kg)	
Complementary Product weight Environment Protective treatment	IP65 conforming to IEC 60529 IP69K 1.83 lb(US) (0.83 kg) TC	
Complementary Product weight Environment Protective treatment Ambient air temperature for storage	IP65 conforming to IEC 60529 IP69K 1.83 lb(US) (0.83 kg) TC -40158 °F (-4070 °C)	
Complementary Product weight Environment Protective treatment	IP65 conforming to IEC 60529 IP69K 1.83 lb(US) (0.83 kg) TC	
Complementary Product weight Environment Protective treatment Ambient air temperature for storage Ambient air temperature for operation Electrical shock protection class	IP65 conforming to IEC 60529 IP69K 1.83 lb(US) (0.83 kg) TC -40158 °F (-4070 °C) -40158 °F (-4070 °C) Class I conforming to IEC 60536	
Complementary Product weight Environment Protective treatment Ambient air temperature for storage Ambient air temperature for operation	IP65 conforming to IEC 60529 IP69K 1.83 lb(US) (0.83 kg) TC -40158 °F (-4070 °C) -40158 °F (-4070 °C) Class I conforming to IEC 60536	
Complementary Product weight Environment Protective treatment Ambient air temperature for storage Ambient air temperature for operation Electrical shock protection class Ordering and shipping details	IP65 conforming to IEC 60529 IP69K 1.83 lb(US) (0.83 kg) TC -40158 °F (-4070 °C) -40158 °F (-4070 °C) Class I conforming to IEC 60536 Class I conforming to NF C 20-030	

Ordering and shipping details

Category	22475 - WALL STATIONS
Discount Schedule	CS2
GTIN	00785901450382

Nbr. of units in pkg.	1
Package weight(Lbs)	2.120000000000001
Returnability	N
Country of origin	MA

Contractual warranty

Warranty period	18 months