Product data sheet Characteristics

XAPM3203

die-cast empty control station - XAPM - Ø22 - zinc alloy - 3 horizontal openings

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 178.00 USD



| | | à |
|-----------------------------|--|---------------------------|
| Range of product | Harmony XAP | |
| Product or component type | Die-cast empty control station | j |
| Device short name | XAPM | |
| Product destination | For Ø 22 mm control and signalling units | <u></u> _ <u></u> <u></u> |
| Product front plate size | 80 x 175 mm | |
| Usable depth | 1.93 in (49 mm) | |
| Number of cut-out | 3 cut-outs | ± |
| Colour of base of enclosure | Blue | : <u>:</u> :: :2 |
| Colour of cover | Blue | <u> </u> |
| Material | Zinc alloy | <u>}</u> |
| Cable entry | 1 hole with blanking plug for cable gland <= 0.71 in (18 mm) 1 hole without blanking plug for cable gland <= 0.71 in (18 mm) | |
| Device mounting | Flush | E |
| IP degree of protection | IP69 conforming to NF C 20-010 IP65 conforming to IEC 60529 IP69K | ilsed for de |
| | | <u>q</u> |

Complementary

| Number of vertical rows | 1 | - 200 |
|-------------------------|-----------------------|--------|
| Product weight | 1.92 lb(US) (0.87 kg) | - 1 |

Environment

| Protective treatment | TC |
|---------------------------------------|--|
| Ambient air temperature for storage | -40158 °F (-4070 °C) |
| Ambient air temperature for operation | -40158 °F (-4070 °C) |
| Overvoltage category | Class I conforming to NF C 20-030 Class I conforming to IEC 60536 |

Ordering and shipping details

| Category | 22475 - WALL STATIONS |
|----------|-----------------------|
| | |

| Discount Schedule | CS2 |
|-----------------------|------------------|
| GTIN | 00785901666257 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 2.18999999999999 |
| Returnability | N |
| Country of origin | MA |

Contractual warranty

| Warranty period | 18 months |
|-----------------|-----------|