

XACS104

spring return contact block - 2 NC - base mounting

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 38.20 USD



Main

Range of product	Harmony XAC
Product or component type	Contact block
Component name	XACS
Electrical circuit type	Control circuit
Contact block type	Single
Type of operator	Spring return
Product compatibility	XACA
Contacts type and composition	2 NC
Mounting of block	Base mounting
Contact operation	Slow-break

Complementary

Connections - terminals	Screw clamp terminals, connection capacity: 1 x 0.5...1 x 2.5 mm ² without cable end Screw clamp terminals, connection capacity: 1 x 0.5...2 x 1.5 mm ² with cable end
Mechanical durability	1000000 cycles
Contact code designation	A600 AC-15, U _e = 240 V, I _e = 3 A conforming to IEC 60947-5-1 appendix A A600 AC-15, U _e = 600 V, I _e = 1.2 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, U _e = 250 V, I _e = 0.27 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, U _e = 600 V, I _e = 0.1 A conforming to IEC 60947-5-1 appendix A
[I _{th} e] conventional enclosed thermal current	10 A
[U _i] rated insulation voltage	600 V (degree of pollution: 3) conforming to IEC 60947-1
[U _{imp}] rated impulse withstand voltage	6 kV conforming to IEC 60947-1
Resistance across terminals	<= 25 MOhm
Operating force	11 N
Short-circuit protection	10 A fuse protection by cartridge fuse type gG
Rated operational power in W	40 W DC-13 for 1000000 cycles, operating rate = 60 cyc/mn at 120 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 48 W DC-13 for 1000000 cycles, operating rate = 60 cyc/mn at 48 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 65 W DC-13 for 1000000 cycles, operating rate = 60 cyc/mn at 24 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C
Terminals description ISO n°1	(11-12)NC

(21-22)NC

Product weight	0.1 lb(US) (0.045 kg)
----------------	-----------------------

Environment

Standards	EN/IEC 60947-5-1 UL 508 CSA C22.2 No 14
-----------	---

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
---------------------------------------	----------------------------

Ambient air temperature for storage	-40...158 °F (-40...70 °C)
-------------------------------------	----------------------------

Vibration resistance	15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6
----------------------	---

Shock resistance	100 gn conforming to IEC 60068-2-27
------------------	-------------------------------------

Overvoltage category	Class II conforming to IEC 61140
----------------------	----------------------------------

Ordering and shipping details

Category	22473 - PUSHBUTTON, PENDANTS
----------	------------------------------

Discount Schedule	CS2
-------------------	-----

GTIN	00785901093336
------	----------------

Nbr. of units in pkg.	1
-----------------------	---

Package weight(Lbs)	0.12
---------------------	------

Returnability	N
---------------	---

Country of origin	CZ
-------------------	----

Contractual warranty

Warranty period	18 months
-----------------	-----------