## Product data sheet Characteristics

# XAPM31

# empty control station - XAP-M - metal - without opening

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 242.00 USD



#### Main

Main		
Range of product	Harmony XAP	
Product or component type	Die-cast empty control station	
Device short name	XAPM	
Product front plate size	80 x 175 mm	
Usable depth	1.93 in (49 mm)	
Number of cut-out	Undrilled	
Colour of base of enclosure	Blue	
Colour of cover	Blue	
Material	Zinc alloy	
Cable entry	1 hole with blanking plug for cable gland with <= 0.71 in (18 mm) 1 hole without blanking plug for cable gland with <= 0.71 in (18 mm)	
Product mounting	Flush mounting	
IP degree of protection	IP69 conforming to NF C 20-010	
in degree of proteodori	IP65 conforming to IEC 60529 IP69K	
	IP65 conforming to IEC 60529	
Complementary Product weight	IP65 conforming to IEC 60529	
Complementary	IP65 conforming to IEC 60529 IP69K	
Complementary Product weight Environment	IP65 conforming to IEC 60529 IP69K	
Complementary Product weight  Environment Protective treatment	IP65 conforming to IEC 60529 IP69K  1.98 lb(US) (0.9 kg)	
Complementary Product weight Environment	IP65 conforming to IEC 60529 IP69K  1.98 lb(US) (0.9 kg)  TC	
Complementary Product weight  Environment Protective treatment Ambient air temperature for storage	IP65 conforming to IEC 60529 IP69K  1.98 lb(US) (0.9 kg)  TC -40158 °F (-4070 °C)	
Complementary Product weight  Environment Protective treatment Ambient air temperature for storage Ambient air temperature for operation Electrical shock protection class	IP65 conforming to IEC 60529 IP69K  1.98 lb(US) (0.9 kg)  TC  -40158 °F (-4070 °C)  -40158 °F (-4070 °C)  Class I conforming to IEC 60536	
Complementary Product weight  Environment Protective treatment Ambient air temperature for storage Ambient air temperature for operation Electrical shock protection class  Ordering and shipping details	IP65 conforming to IEC 60529 IP69K  1.98 lb(US) (0.9 kg)  TC  -40158 °F (-4070 °C)  -40158 °F (-4070 °C)  Class I conforming to IEC 60536	
Complementary Product weight  Environment Protective treatment Ambient air temperature for storage Ambient air temperature for operation	IP65 conforming to IEC 60529 IP69K  1.98 lb(US) (0.9 kg)  TC  -40158 °F (-4070 °C)  -40158 °F (-4070 °C)  Class I conforming to IEC 60536 Class I conforming to NF C 20-030	

#### Complementary

Product weight	1.98 lb(US) (0.9 kg)
----------------	----------------------

## Environment

Protective treatment	TC	—ţ
Ambient air temperature for storage	-40158 °F (-4070 °C)	_ 6
Ambient air temperature for operation	-40158 °F (-4070 °C)	— t
Electrical shock protection class	Class I conforming to IEC 60536 Class I conforming to NF C 20-030	

#### Ordering and shipping details

Category	18406 - WORLD SERVICE PARTS(OTHER OP INT)
Discount Schedule	CS2
GTIN	00785901401278

Nbr. of units in pkg.	1
Package weight(Lbs)	2.2200000000000002
Returnability	N
Country of origin	MA

## Contractual warranty

Warranty period	18 months