Product data sheet Characteristics

XZCE13M785M

adaptor, metal - tapped hole Pg 13.5 - for male connector, 7/8" 16UN, 5-wire

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 37.20 USD



Main

		The state of the s
Accessory / separate part designation	5-wire connector adaptor	
Accessory / separate part category	Cabling accessories	
Accessory / separate part type	Connector adaptor	90
Cable composition	5 x 1 mm²	ភ
Thread type	Pg 13.5	
Line Rated Current	6 A	

Complementary

Cable length	3.94 in (100 mm)	
Total number of wires	5	
Electrical connection	1 male connector 5 straight	
Cable connector fixing	Screw-on	
Body material	Metal	
Insulation resistance	> 1000000000 Ohm	
Resistance across terminals	<= 5000 mOhm	
System Voltage	250 V AC 300 V DC	
Product weight	0.11 lb(US) (0.05 kg)	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-13176 °F (-2580 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES	ation
Discount Schedule	DS3	
GTIN	003389110868760	
Nbr. of units in pkg.	1	
Package weight(Lbs)	8.99999999999997E-2	

Returnability	N	
Country of origin	PL	
Offer Sustainability		
RoHS (date code: YYWW)	Compliant - since 9830 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	

18 months

Warranty period