

Product data sheet

Characteristics

XACA06H7

empty pendant control station XAC-A - 6 vertical openings

Product availability : Stock - Normally stocked in distribution facility

Price* : 306.00 USD



Main

| | |
|---------------------------|-------------------------|
| Range of product | Harmony XAC |
| Product or component type | Pendant control station |
| Device short name | XACA |

Complementary

| | |
|---------------------------------------|--|
| Control station type | Double insulated |
| Enclosure material | Polypropylene |
| Electrical circuit type | Control circuit |
| Enclosure type | Empty enclosure |
| Number of cut-out | 6 cut-outs |
| Control station colour | Yellow |
| Cable entry | Rubber sleeve with stepped entry 8...26 mm |
| Guard rail | Without |
| Vertical operator cut-out centre | 1.18 in (30 mm) |
| Standards | EN/IEC 60204-32 EN/IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| Product certifications | CCC CSA GOST UL |
| Protective treatment | TH |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 15 gn 10...500 Hz IEC 60068-2-6 |
| Shock resistance | 100 gn IEC 60068-2-27 |
| Overvoltage category | Class II IEC 61140 |
| IP degree of protection | IP65 IEC 60529 |
| IK degree of protection | IK08 EN 50102 |
| Mechanical durability | 1000000 cycles |
| Product weight | 1.47 lb(US) (0.665 kg) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

| | |
|-----------------------|------------------------------|
| Category | 22473 - PUSHBUTTON, PENDANTS |
| Discount Schedule | CS2 |
| GTIN | 00785901306498 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.6899999999999999 |
| Returnability | Y |
| Country of origin | CZ |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|