



Representative

**Catalog Number:** 3143  
**Product ID:** 7TAA106030R0020  
**UPC Number:** 78621003143  
**Status:** Active

Metal-Clad and Armored Cable Fitting, 90 Degree Bend, Trade Size 3-1/2 Inch, Knockout Size 3 Inch, Cable Range 3.620 to 4.060 Inch, Malleable Iron with Zinc Plating, Nylon Insulated

- All the advantages of the straight connector with only one screw to tighten, except in the larger sizes where there are two.
- A peep hole on top provides for easy inspection of the ABC bushing.
- Narrow design makes it easy to install connectors in adjacent knockouts.
- To connect and effectively bond armored cable or flexible metal conduit to a box or an enclosure.

### Header

3D Model Available on Website

### North American Specifications (UNSPSC)

UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B
Type	Armored Cable/Flexible Metal Conduit Fittings
Special Features	By Far The Easiest and Best to Install When Making Sharp Bends At The Enclosure or Equipments
Application	For Use with Armored Cable and Flexible Metal Conduit
Standard	UL E23018
Size	3-1/2 Inch
Connection	90 Degree
Conductor Range	3.620 to 4.060 Inch
Material	Malleable Iron
Finish	Electro Zinc Plated
Color	Metallic
Insulation	Nylon

### European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	3 1/2 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Other
Material housing	Other
Surface protection	Zinc coated
Thread length	26.98mm

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	10.1x6.8x8.2
Weight Uom	1033 lbs. per 100

### Documents / Support Tools

Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)