

**Catalog Number:** CPO125-5-C  
**Product ID:** 7TAA017310R0047  
**UPC Number:** 78621083370  
**Status:** Active



Thin-Wall Heat-Shrinkable Tubing for Cable Range 30 - 24 AWG, Expanded Diameter 1/8, Length 100 feet reel, rated for 600 Volt, 125 degrees C, Material: Cross-linked polyolefin - Non-lined, Green

- Flame-retardant, cross-linked polyolefin.
- Meets UL 224, 125°C; CSA 22.2 No. 198.1, 125°C; MIL-DTL-23053/5 Class 1&2; AMS 3636 & 3637; DEF STAN 59-97, Issue 3, Type 2a

Actual

### North American Specifications (UNSPSC)

|                  |   |
|------------------|---|
| UNSPSC           | 39121723 Heat shrinkable tube             |
| IGCC             | 5073 Heat shrinkable tube                 |
| Brand Name       | Shrink-Kon                                |
| Type             | Thin-Wall Heat-Shrinkable Tubing          |
| Special Features | Flame-retardant, cross-linked polyolefin. |
| Shrink Ratio     | 2:1                                       |
| Thickness        | Thin                                      |
| Length           | 100                                       |
| Color            | Green                                     |

### European Specifications (ETIM)

|                                   |                        |
|-----------------------------------|------------------------|
| ETIM                              | EC000217 Shrink tubing |
| Type                              | Heat-shrink            |
| Model                             | Thin-walled            |
| Shrink rate                       | 2:1                    |
| Inner diameter before heat-shrink | 3.302mm                |
| Inner diameter after heat-shrink  | 1.524mm                |
| Nominal diameter inch             | 1/8 inch               |
| Wall thickness after shrinking    | 0.508mm                |
| Length                            | 30.48m                 |
| Operation temperature             | -55-+135°C             |
| Colour                            | Green                  |
| Material                          | Polyolefin (PO-X)      |
| Halogen free                      | N                      |
| With inner glue                   | N                      |
| Printable                         | N                      |
| UL approval                       | Y                      |

### Packaging

|                           |                |
|---------------------------|----------------|
| Outer Quantity            | 1              |
| Outer Dimensions (inches) | 9.5x9.5x3.1    |
| Weight Uom                | 2.75 lbs. Each |

### Documents / Support Tools

|                         |                      |
|-------------------------|----------------------|
| Technical Data Sheet US | Available on Website |
| Technical Data Sheet CA | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)