

C41 UK Wall Mount 8VA Transformer Series

Features

- 230 VAC Input
- UK Wall Plug Style
- Rated for Continuous Duty
- AC outputs up to 8VA
- Meets Safety Agency Requirements
- Complies with EMI/RFI Regulations
- CE Compliant
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking Available
- 1 Year Warranty
- Modified and Custom Designs Also Available
- Manufactured in China

Ault Model	Rated Output Volts AC	Maximum Current-Amps	Maximum VA
C41-061333-A000G	6	1.33	8.0
C41-071140-A000G	7	1.14	8.0
C41-081000-A000G	8	1.00	8.0
C41-090700-A000G	9	0.70	6.3
C41-100800-A000G	10	0.80	8.0
C41-110727-A000G	11	0.73	8.0
C41-120667-A000G	12	0.67	8.0
C41-150533-A000G	15	0.53	8.0
C41-160500-A000G	16	0.50	8.0
C41-180444-A000G	18	0.44	8.0
C41-200400-A000G	20	0.40	8.0
C41-220364-A000G	22	0.36	8.0
C41-240333-A000G	24	0.33	8.0

*To be assigned at time of order placement

Input

- Voltage 230 VAC
- Line Frequency 50 Hz
- Connector UK Wall Plug, No Ground

Electrical

- Topology Step Down AC/AC Transformer
- Dielectric Withstand 3000 VAC primary-secondary
1500 VAC primary-core
500 VAC secondary-core
- Protection Current, Thermal or Energy Limiting
- EMI Complies with EMC Directives
- CE CE Compliant

Safety Approvals

- Safety Agencies TUV EN60950

Environmental

- Operating Temperature 0° to 40° C with no derating
- Storage Temperature -30° to +85° C
- Relative Humidity 5% to 95% non-condensing
- Altitude 0-10,000 feet
- Cooling Convectional - non vented case

Mechanical

- Case Dimensions C41 - UK Wall Plug
2.8 L x 2.0 W x 1.8H (in)
72 L x 51 W x 46 H (mm)
- Case Material Black 94 V1 Polycarbonate
- Weight 12 ounces, 350 grams,
(excluding cord)
- Cord and Connector 6 ft., 2 Conductor, 22-24 AWG
Ault #3 Connector
Other Connectors Available

ONE YEAR WARRANTY

