



### Main

Range	TeSys
Device short name	GVAU
Product or component type	Undervoltage trip
Product compatibility	GV2L GV2LE GV2ME GV2P GV3L GV3P

### Complementary

Control circuit voltage	220...240 V AC 50 Hz
Control circuit voltage limits	0.85...1.1 Un
[Ui] rated insulation voltage	600 V AC CSA C22.2 No 14 690 V AC IEC 60947-1 600 V AC UL 508
Threshold tripping voltage	0.7...0.35 Un
Inrush power in VA	12 VA AC
Inrush power in W	8 W DC
Hold-in power consumption in VA	3.5 VA AC
Hold-in power consumption in W	1.1 W DC
Operating time	10...15 ms IEC 60947-1
On-load factor	100 %
Connections - terminals	Screw clamp terminals 2 0.75...1.5 mm <sup>2</sup> flexible with Screw clamp terminals 1 0.75...1.5 mm <sup>2</sup> flexible with Screw clamp terminals 2 1...2.5 mm <sup>2</sup> solid Screw clamp terminals 2 0.75...2.5 mm <sup>2</sup> flexible without Screw clamp terminals 1 1...2.5 mm <sup>2</sup> solid Screw clamp terminals 1 0.75...2.5 mm <sup>2</sup> flexible without
Tightening torque	<= 1.4 N.m screw clamp terminals
Mechanical durability	30000 cycles with GV2ME and GV2P 10000 cycles with GV3P and GV3L
Quantity per set	Set of 10
Product weight	0.105 kg

### Contractual warranty

Period	18 months
--------	-----------