

Product data sheet

Characteristics

XAPG49400

die-cast empty control station - XAP-G - Ø22 - undrilled

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 174.00 USD



Main

Range of product	Harmony XAP
Product or component type	Die-cast empty control station
Device short name	XAPG
Product destination	For Ø 22 mm control and signalling units
Number of cut-out	Undrilled
Colour of base of enclosure	Grey RAL 7032
Colour of cover	Grey RAL 7032
Material	Zinc alloy
Cable entry	1 hole with blanking plug for cable gland with ≤ 0.55 in (14 mm) 1 hole without blanking plug for cable gland with ≤ 0.55 in (14 mm)
Product mounting	Flush mounting
IP degree of protection	IP65 conforming to IEC 60529 IP657 conforming to NF C 20-010

Complementary

Number of vertical rows	0
-------------------------	---

Environment

Protective treatment	TC
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Electrical shock protection class	Class I conforming to IEC 60536 Class I conforming to NF C 20-030

Ordering and shipping details

Category	22475 - WALL STATIONS
Discount Schedule	CS2
GTIN	00785901186953
Nbr. of units in pkg.	1
Package weight(Lbs)	3.52

Returnability	N
Country of origin	MA

Contractual warranty

Warranty period	18 months
-----------------	-----------
