



Actual



Representative

Catalog Number: 2237
Product ID: 7TBD105140R0004
UPC Number: 78621002237
Status: Active

Service Entrance Cable Connector, 3/4 Inch, Die Cast Zinc, Gland-Steel-Electro Zinc Plated, Retaining Ring-Stainless Steel, Bushing-Neoprene, Cable Opening 0.230 x 0.430 Inch

- Taper threaded body, stainless steel retaining ring protects cable jacket against abrasion; reduces installing torque effort.
- Rugged ribbed steel gland construction, suitable for Type SE & USE service entrance cable.

Header

3D Model Available on Website

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Type	Underground Feeder Cable Connectors
Special Features	Neoprene Bushing, Resists Oil and Water; Grips Cable The Full Length of The Bushing Providing Adequate Strain Relief Without Damaging Outer Jacket.
Application	To Connect Service Entrance Cables to a Meter Box or an Enclosure.
Standard	UL E17583, CSA
Size	3/4 Inch
Conductor Range	0.230 x 0.430 Inch
Material	Zinc Die Cast
Color	Metallic

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	3/4 inch
Thread length	14.288mm
Suitable for cable diameter	5.842-10.922mm
Material	Metal
Material quality	Other
Surface protection	Galvanic/electrolytic zinc plated
Colour	Natural colour
Model	Straight
Type of sealing	Sealing ring

Packaging

Inner Quantity	10
Inner Dimensions (inches)	4x4x3
Outer Quantity	100
Outer Dimensions (inches)	21.9x3.8x8.89
Weight Uom	19.5 lbs. per 100

Documents / Support Tools

Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com