
# Thomas&Betts



Actual



**GRUPE-100-9-C** 7TAG009750R0049 72849410910 05414363023838 Active

Extruded Grommeting, Natural Un-Cut Polyethylene for Temperatures up to 85 Degrees Celsius (185 F), Height of 5.58mm (0.220 Inches), Width of 5.33mm (0.21 Inches), Thickness 1.14mm (0.045 Inches), Width Maximum Panel Thickness of 2.54mm (1.05 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 .250 inches thick and in a variety of stocked materials to cover a wide range of applications.
- Application Tools: SR-100

North American Specifications (UNSPSC)		
UNSPSC	39131603 Grommet edging	
IGCC	5393 Grommet edging	
Brand Name	Catamount	
Туре	Grommeting	
Special Features	Used to line panel edges and knockouts where the	
	chafing of wires is a concern.	
Color	Natural	
Panel Thickness	0.100	
Material	Un-Cut Polyethylene	

## **European Specifications (ETIM)**

	· · · ·	
ETIM		EC002604 Cable bundle hose
Material		Plastic
Material quality		Polyethylene
Colour		Natural colour
Transparent		N

# Packaging

Packaging	
Inner Quantity	1
Inner Dimensions (inches)	17x12x1.75
Outer Quantity	10
Outer Dimensions (inches)	18x12.5x12
Weight Uom	1.18 lbs. Each

### **Documents / Support Tools**

Technical Drawing / Data Sheet Canada Available on Website

#### For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com